

12.3 Using Open GIS web services to serve environmental data

12.3 Using Open GIS web services to serve environmental data

Daryl Herzmann

Raymond Arritt



Iowa Environmental Mesonet (IEM)

Department of Agronomy, Iowa State University



Our GIS Session History

- 2003: Getting our data into GIS accessible formats. Spatial Databases
- 2004: GIS Web Mapping. Applications with NEXRAD information.




The rundown for 2005!

- Motivation
- Overview of OGC web services (WMS, WFS, WCS)
- IEM web service offerings
- Example implementations
- What we have learned



12.3 Using Open GIS web services to serve environmental data



The Software Components



Good evening Mr. Gates, I'll be your server today!



PostGIS – Spatial database for the PostgreSQL RDBM

MapServer – Extremely fast and capable internet mapping server also supporting WFS, WMS, WCS

Linux – What else would you build your enterprise data system on?



WMS: Web Map Service

- “A WMS produces maps of spatially referenced data dynamically from geographic information.” - from OGC WMS 1.3
- WMS defines three operations protocols
 - GetCapabilities
 - Get server capabilities
 - GetMap
 - Returns a map or an exception
 - GetFeatureInfo (Optional)
 - Mechanism to do pixel queries on GetMap generated maps



WFS: Web Feature Service

- “[WFS] proposes interfaces for describing data manipulation operations on geographic features using HTTP” – OGC WFS 1.0
- Data manipulation operations include
 - Create a new feature instance
 - Delete a feature instance
 - Update a feature instance
 - Get or query features based on spatial constraint



WCS: Web Coverage Service

- “WCS supports electronic exchange of geospatial data as ‘coverages’ ” – OGC WCS 1.0
- A WCS provides three operations
 - GetCapabilities
 - GetCoverage
 - DescribeCoverage



12.3 Using Open GIS web services to serve environmental data

Simple OGC Client & Server Session

Step 1: Only done once

Request Capabilities

XML encoded Capabilities

OGC Client

Step 2: Optional request for metadata

Client asks for metadata

Server responds with metadata (XML)

OGC Server

Step n: Data communication

Client asks for data

Server responds with data



12.3 Using Open GIS web services to serve environmental data

IEM OGC Offerings

<http://mesonet.agron.iastate.edu/ogc/>

	WMS	WFS	WCS
CONUS NEXRAD (Base Reflect, Storm Precip)	X		? X ?
NCEP Stage4 Precip (Iowa)	X	X	
Iowa Road Conditions	X	X	
NWS Current/Archived Warnings (County + Polygon)	X	X	



Supporting 2004 Hurricanes


Provided Disaster Management Interoperability Services a RADAR WMS to support their decision support software

<http://www.cmi-services.org>




Providing Road Conditions to Media Outlets

- WFS and WMS support generation of images for display in TV Weather graphics systems



NWS Warnings WFS

- Retrieve current and historical NWS warnings (polygon and county based).
- Archive begins Jul 2002



Lessons Learned

- OGC webservices greatly reduced chaos on our server. Chaos being:
 - Redundantly storing data for different apps
 - Versioning issues with redundant data
 - Redundant code to simply add a RADAR layer to a map
- The application development time reduced
- Performance hit was remarkably small



More Lessons Learned

- Often, the performance bottleneck is the overhead of HTTP
- The client application/implementation is absolutely key
 - Example: No WFS support for ArcGIS9 (?)
- (Daryl's 2 cents) The OSS community needs to generate some killer OGC desktop interfaces and scripting libraries. [PyOGCLib a start?]



Time for Questions?



mesonet.agron.iastate.edu

Daryl Herzmann

515.294.5978

Akrherz@iastate.edu

